

Q20A

ECONOMIC 2000:1 HIGH ACCURACY MINI 100A CURRENT CLAMP SENSOR

The model Q20A 100A current clamp sensor is ideal for using with electronic meter or other device with AC current input, it is suitable for 100A cable online measurement, max 200A. Only weight 300g, it has high accuracy class 0.1% and wide frequency range from 10Hz to 20KHz. Clamp type structure and non-contact measurement, easy to operate, fast, safe and reliable. it can be used for power analyzer, watt-hour meter tester & smart power meter.

Application

1. Multimeter;
2. Power meter;
3. Energy meter;
4. Phase angle meter;
5. Energy sub-meters;
6. Oscilloscopes meter;
7. Data logging/recording;
8. Power load monitoring;
9. Energy meter field tester;
10. Power and harmonic meters;
11. Power quality analyzer(PQA);
12. Measuring around cable bundles;



Features

1. UL, CE, CNAS mark;
2. With load capacity $\leq 10\Omega$;
3. Small, compact size;
4. With harmonic measurement;
5. Holding wire diameter: $\phi 20\text{mm}$;
6. Frequency 10Hz-20KHz Bandwidth;
7. Low phase shift for power measurement;
8. Measurement range of 1mA to 200A AC;
9. High content nickel metal permalloy core;
10. Conforms to EN 61010-2-032, 600V CAT III;
11. High precision 0.1% for current measurement;
12. Improved ergonomic design & easy operation;
13. Designed for DMMs, recorders, calibrators, power and harmonic testers;

Parameters

Electrical parameters	
Ratio	1000:1, 2000:1 or 2500:1 (customized)
Accuracy class	0.1%, 0.2%, 0.5%
Primary current	0 - 100A AC, 0 - 200A AC
Secondary current	0 - 100mA AC, 0 - 200mA AC (customized)
Max. Cont. Input current	240A
Load capacity	$\leq 10\Omega$, Standard 4Ω
Over voltage category	CAT III 600V
Output signal (AC current)	From 0 to 200mA AC at nominal input current
Output signal (AC voltage)	From 0 to 200mV AC at nominal input current
Frequency range	40Hz-20000Hz
Signal ratio	1mA/A, 1mV/A, 10mV/A, 100mV/A
Dielectric strength	3KV 50Hz/60Hz at 1 minute
Temperature range	-20°C to +55°C
Output	2.5 meter cable with D01 connector
Max. voltage not insulated conductors	720 V
Standard	EN 61010-1, EN 61010-2-032, EN 61010-2-031 IEC60044-1, & IEC61869-2, 600V CAT III
Installation	Clamp type
Output mode	Lead output (2.5m)
Connector	BNC, 4mm banana, Audio plug, customized
Mechanical parameters	
Dimensions (L x W x H) (mm)	48 x 186 x 27
Weight (g)	300
Holding wire diameter (mm)	$\phi 20$
Max. jaw opening (mm)	20
Color	Black
Material	PC+ABS+Polycarbonate, UL94 VO

Selection guide

Model	Rate Current	Max Current	Secondary	Coil Ratio	Burden Resistance	Accuracy
Q20A-10-1	10A	12A	10mA	1000:1	customized	0.1%
Q20A-10-2	10A	12A	5mA	2000:1	customized	0.1%
Q20A-10-3	10A	12A	4mA	2500:1	customized	0.1%
Q20A-20-1	20A	24A	20mA	1000:1	customized	0.1%
Q20A-20-2	20A	24A	10mA	2000:1	customized	0.1%
Q20A-20-3	20A	24A	8mA	2500:1	customized	0.1%
Q20A-100-1	100A	120A	100mA	1000:1	customized	0.1%
Q20A-100-2	100A	120A	50mA	2000:1	customized	0.1%
Q20A-100-3	100A	120A	40mA	2500:1	customized	0.1%
Q20A-200-1	200A	240A	200mA	1000:1	customized	0.1%
Q20A-200-2	200A	240A	100mA	2000:1	customized	0.1%
Q20A-200-3	200A	240A	80mA	2500:1	customized	0.1%
Q20A-V10-1	10A	50A	100mV	1000:1	customized	0.1%
Q20A-V10-2	10A	12A	1V	1000:1	customized	0.1%
Q20A-V10-3	10A	12A	5V	1000:1	customized	0.1%
Q20A-V20-1	20A	50A	200mV	1000:1	customized	0.1%
Q20A-V20-2	20A	24A	2V	1000:1	customized	0.1%
Q20A-V20-3	20A	24A	5V	1000:1	customized	0.1%
Q20A-V100-1	100A	120A	100mV	1000:1	customized	0.1%
Q20A-V100-2	100A	120A	1V	1000:1	customized	0.1%
Q20A-V100-3	100A	120A	5V	1000:1	customized	0.1%
Q20A-V200-1	200A	240A	200mV	1000:1	customized	0.1%
Q20A-V200-2	200A	240A	2V	1000:1	customized	0.1%
Q20A-V200-3	200A	240A	5V	1000:1	customized	0.1%
Q20A-5-12	5A	6A	5mA	1000:1	customized	0.2%
Q20A-5-22	5A	6A	2.5mA	2000:1	customized	0.2%
Q20A-5-32	5A	6A	2mA	2500:1	customized	0.2%
Q20A-10-12	10A	12A	10mA	1000:1	customized	0.2%
Q20A-10-22	10A	12A	5mA	2000:1	customized	0.2%
Q20A-10-32	10A	12A	4mA	2500:1	customized	0.2%
Q20A-20-12	20A	24A	20mA	1000:1	customized	0.2%
Q20A-20-22	20A	24A	10mA	2000:1	customized	0.2%
Q20A-20-32	20A	24A	8mA	2500:1	customized	0.2%
Q20A-100-12	100A	120A	100mA	1000:1	customized	0.2%
Q20A-100-22	100A	120A	50mA	2000:1	customized	0.2%
Q20A-100-32	100A	120A	40mA	2500:1	customized	0.2%
Q20A-V5-12	5A	50A	50mV	1000:1	customized	0.2%
Q20A-V5-22	5A	6A	500mV	1000:1	customized	0.2%
Q20A-V5-32	5A	6A	1V	1000:1	customized	0.2%



Q20A

AC CURRENT CLAMP

Model	Rate Current	Max Current	Secondary	Coil Ratio	Burden Resistance	Accuracy
Q20A-V10-12	10A	50A	100mV	1000:1	customized	0.2%
Q20A-V10-22	10A	12A	1V	1000:1	customized	0.2%
Q20A-V10-32	10A	12A	5V	1000:1	customized	0.2%
Q20A-V20-12	20A	50A	200mV	1000:1	customized	0.2%
Q20A-V20-22	20A	24A	2V	1000:1	customized	0.2%
Q20A-V20-32	20A	24A	5V	1000:1	customized	0.2%
Q20A-V100-12	100A	120A	100mV	1000:1	customized	0.2%
Q20A-V100-22	100A	120A	1V	1000:1	customized	0.2%
Q20A-V100-32	100A	120A	5V	1000:1	customized	0.2%
Q20A-V200-12	200A	240A	200mV	1000:1	customized	0.2%
Q20A-V200-22	200A	240A	2V	1000:1	customized	0.2%
Q20A-V200-32	200A	240A	5V	1000:1	customized	0.2%

Notes: Can be customized current probe according to user requirements!