

XQ13

HIGH PERFORMANCE 100A AC AMP CURRENT PROBE CLAMP

The model XQ13 100A current probe clamp is suitable for 0A-100A cable online measurement, it belongs to high performance transducer field. Up to 0.1% accuracy class, this current probe clamp is suitable for most oscilloscopes. Current signal can be measured directly. Suitable for accurate measurement of AC current using the permalloy core material. Frequency range 40Hz-200KHz, with standard 2.5 meter cable with D01 connector. EN 61010-1, EN 61010-2-032, IEC60044-1 Standard.

Application

1. Multimeter;
2. Power meter;
3. Digital multi-meter;
4. Energy sub-meters;
5. Phase angle meter;
6. Oscilloscopes meter;
7. Power quality analyzer;
8. Data logging/recording;
9. Power load monitoring;
10. Power quality monitoring;
11. Power and harmonic meters;
12. Multi-function energy meter;
13. CT secondary current detection;
14. Energy meter calibrator (on site);
15. Measuring around cable bundles;



Features

- | | |
|--|--------------------------------------|
| 1. Holding wire diameter: ϕ 13mm; | 2. UL, CE, CNAS mark; |
| 3. Measurement range of 1mA to 120A AC; | 4. Small, compact size; |
| 5. Low phase shift for power measurement; | 6. 1mA/A AC output signals; |
| 7. Improved ergonomic design and easy operation; | 8. 40Hz to 200kHz response; |
| 9. Designed to EN 61010, 600V CAT III safety standard; | 10. Installation: clamp type design; |
| 11. Designed for DMMs, loggers, recorders and oscilloscopes; | 12. High content nickel metal core; |
- Suitable for 5A, 10A, 20A, 50A, 100A cable online measurement;

Parameters

Electrical parameters

Ratio	1000: 1, 2000:1 or 2500:1 (customized)
Accuracy class	0.1%, 0.2%
Primary current	0 - 100A AC
Secondary current	0 - 100mA AC (customized)
Max. Cont. Input current	120A
Load capacity	$\leq 20\Omega$, Standard 4Ω
Over voltage category	CAT III 600V
Output signal (AC current)	From 0 to 100mA AC at nominal input current
Output signal (AC voltage)	From 0 to 5V AC at nominal input current
Signal ratio	1mA/A, 1mV/A, 10mV/A, 100mV/A
Frequency range	40Hz-200KHz
Dielectric strength	3KV 50Hz/60Hz at 1 minute
Temperature range	-20°C to +55°C
Output	2.5 meter cable with D01 connector
Max. voltage not insulated conductors	720 V
Standard	EN 61010-1, EN 61010-2-032, EN 61010-2-031 IEC60044-1, & IEC61869-2, 600V CAT III
Installation	Clamp type
Output mode	Lead output (2.5m)
Connector	BNC, 4mm banana, Audio plug, customized

Mechanical parameters

Dimensions (L x W x H) (mm)	48 x 179 x 27
Weight (g)	325
Holding wire diameter (mm)	$\phi 13$
Max. jaw opening (mm)	13
Jaw color	Red, yellow, blue, green, black
Material	PC+ABS+Polycarbonate, UL94 VO

Selection guide

Model	Rate Current	Max Current	Secondary	Coil Ratio	Burden Resistance	Accuracy
XQ13-5-1	5A	6A	5mA	1000:1	customized	0.1%
XQ13-5-2	5A	6A	2.5mA	2000:1	customized	0.1%
XQ13-5-3	5A	6A	2mA	2500:1	customized	0.1%

Model	Rate Current	Max Current	Secondary	Coil Ratio	Burden Resistance	Accuracy
XQ13-10-1	10A	12A	10mA	1000:1	customized	0.1%
XQ13-10-2	10A	12A	5mA	2000:1	customized	0.1%
XQ13-10-3	10A	12A	4mA	2500:1	customized	0.1%
XQ13-20-1	20A	24A	20mA	1000:1	customized	0.1%
XQ13-20-2	20A	24A	10mA	2000:1	customized	0.1%
XQ13-100-1	100A	120A	100mA	1000:1	customized	0.1%
XQ13-100-2	100A	120A	50mA	2000:1	customized	0.1%
XQ13-100-3	100A	120A	40mA	2500:1	customized	0.1%
XQ13-V5-1	5A	50A	50mV	1000:1	customized	0.1%
XQ13-V5-2	5A	6A	500mV	1000:1	customized	0.1%
XQ13-V5-3	5A	6A	1V	1000:1	customized	0.1%
XQ13-V10-1	10A	50A	100mV	1000:1	customized	0.1%
XQ13-V10-2	10A	12A	1V	1000:1	customized	0.1%
XQ13-V10-3	10A	12A	5V	1000:1	customized	0.1%
XQ13-V100-1	100A	120A	100mV	1000:1	customized	0.1%
XQ13-V100-2	100A	120A	1V	1000:1	customized	0.1%
XQ13-V100-3	100A	120A	5V	1000:1	customized	0.1%
XQ13-5-12	5A	6A	5mA	1000:1	customized	0.2%
XQ13-5-22	5A	6A	2.5mA	2000:1	customized	0.2%
XQ13-5-32	5A	6A	2mA	2500:1	customized	0.2%
XQ13-10-12	10A	12A	10mA	1000:1	customized	0.2%
XQ13-10-22	10A	12A	5mA	2000:1	customized	0.2%
XQ13-10-32	10A	12A	4mA	2500:1	customized	0.2%
XQ13-20-12	20A	24A	20mA	1000:1	customized	0.2%
XQ13-20-22	20A	24A	10mA	2000:1	customized	0.2%
XQ13-100-12	100A	120A	100mA	1000:1	customized	0.2%
XQ13-100-22	100A	120A	50mA	2000:1	customized	0.2%
XQ13-100-32	100A	120A	40mA	2500:1	customized	0.2%
XQ13-V5-12	5A	50A	50mV	1000:1	customized	0.2%
XQ13-V5-22	5A	6A	500mV	1000:1	customized	0.2%
XQ13-V5-32	5A	6A	1V	1000:1	customized	0.2%
XQ13-V10-12	10A	50A	100mV	1000:1	customized	0.2%
XQ13-V10-22	10A	12A	1V	1000:1	customized	0.2%
XQ13-V10-32	10A	12A	5V	1000:1	customized	0.2%
XQ13-V100-12	100A	120A	100mV	1000:1	customized	0.2%
XQ13-V100-22	100A	120A	1V	1000:1	customized	0.2%
XQ13-V100-32	100A	120A	5V	1000:1	customized	0.2%

Notes: Can be customized current probe according to user requirements!