

T-3630E

ADVANCED MULTIFUNCTION EARTH GROUND RESISTANCE TESTER

T-3630E advanced multifunction earth ground resistance tester specially design for the measurement of earth resistance, soil resistivity, earth voltage, leakage current of grounding line, AC current, DC resistance. Adopting the latest digital technology, precise 4-pole, 3-pole and simple 2-pole method, selection method, double clamp method to measure grounding resistance, for earth resistance measurement; large caliber clamp design, used to measure the grounding system which adopt large-scale down conductor; can flexibly and precisely measure the value of grounding resistance in every complicated situation like single point grounding, grounding mesh.

T-3630E earth resistance tester is not need to disconnect any parallel connection pole when measuring parallel-grounding, and massively improve the convenience when measuring. Importing FFT and AFC technology, with a unique function of anti-interference capability and the ability to adapt to the environment, consistency of repeat testing, to ensure high precision, stability and reliability for prolonged measure, which is widely used in electric power, telecommunications, meteorology, oil field, construction, lightning protection, industrial electrical equipment and other earth resistance, soil resistivity, earth voltage, AC voltage measurement.

T-3630E multifunction earth ground resistance meter is composed of host machine, PC monitoring software, test leads, auxiliary ground pillars, communication wires and others. The 5inch TFT color LCD display of host machine is with touch that can be seen clearly. At the same time it can store 500 sets of data, fulfilling historical inquiry and online real-time monitoring through monitoring software, dynamic display, and alarm indicator, auto-shut down and with the functions like historical data access, reading, preservation, report forms, printing and so on.



Functions

1. Selection method;
2. 3-pole measurement;
3. Testing Soil resistivity;
4. Double clamp method;
5. AC voltage measurement;
6. Precise 4-pole measurement;
7. Simple 2-pole measurement;
8. Measure grounding resistance;
9. Measurement of earth voltage;
10. AC leakage current measurement;

Features

1. Accuracy 2%;
2. AC voltage 0-750V;
3. DC voltage 0-1000V;
4. With IP65 protection;
5. Recorder 500 sets data;
6. With touch TFT color LCD;
7. With thermal printer optional;
8. AC current measurement 0-1000A;
9. Soil Resistivity (ρ) 0.00 Ω m - 9999k Ω m;
10. Earth resistance range 0.00 Ω - 200.00k Ω ;

Parameters

Electrical parameters

Model	T-3630E-A 2/3/4-wire, 0.00k Ω ~200.00k Ω , 0.00 Ω m-9999k Ω m T-3630E-B 2/3/4-wire, 0.00k Ω ~200.00k Ω , 0.00 Ω m-9999k Ω m with printer T-3630E-C 2/3/4-wire, 0.00k Ω ~200.00k Ω , 0.00 Ω m-9999k Ω m, 1000A double clamp on ct, with printer
Function	Two/Three/Four-wire AC ground resistance- Soil resistivity, Three/Four-wire selective method, Dual-clamp resistance, DC resistance, AC voltage, AC current, DC voltage
Accuracy	2%
Power Supply	DC 12V(4.5AH battery, continuous standby for 300 hours)
Measuring Mode	Precise 4-pole measurement, 3-pole measurement, simple 2-pole measurement, selection method, double clamp method measure
Measuring Method	2/3/4-wire method measurement: Polarity - changing method, measurement current 42.0mA Max Soil resistivity: Four - pole method Selective measurement: Polarity - changing method, measurement current 42.0mA Max Dual - clamp method: Non - contact mutual induction measurement method, test current 40mA Max DC resistance: Polarity - changing method AC current: Average value rectification (clamp - type) Ground voltage: Average value rectification (between S - ES interfaces) DC voltage: Average value rectification (between S - ES interfaces)
Measuring Rate	AC current: about 2 times/second Voltage to ground: about 2 times/second Earth resistance, soil resistivity: about 7 seconds/time
Measuring Times	Over 5000 times (Short-circuit test, interval time should be at least 30
Earth resistance range	0 Ω - 200.00K Ω
Resolution	0.01 Ω /0.1 Ω /1 Ω /10 Ω
Soil resistivity range	0.00 Ω m - 9999k Ω m

Electrical parameters - continued

Resolution	0.01Ωm/0.1Ωm/1Ωm/10Ωm/100Ωm/1kΩm
Earth Voltage Range	0 - 750V; Resolution: 0.01V
Clamp AC current Range	0 - 1000A; Resolution: 0.1mA
Test Voltage Wave	Sine wave
Test Frequency	128Hz
Short-circuit Test Current	AC 42mA max
Open-circuit Test Current	AC 30.0V Max DC 30.0V Max
Electrode Interval Range	0.1m-100.0m
LCD display	Color - display screen, 5 inch touch, 850×480, 108 mm×65mm
Communication	USB Port
Data Storage	500 GROUPS
Alarm Function	Yes
Power Consumption	Screen brightness: 190mA Max(maximum brightness) 140mA Min(minimum brightness) Measurement: 200mA Max(maximum brightness) 150mA Min(minimum brightness)
Overload Protection	Measurement of ground-to -earth voltage: H - E, S - E (port - to - port) AC 280V/3 seconds
Insulation Resistance	Over 20MΩ (between circuit and enclosure it is 500V)
Withstand voltage	AC 3700V/rms. (between the circuit and the shell)
Standard	IEC61010-1 (CAT III 300V, CAT IV 150V, pollution degree 2); IEC61010-031; IEC61557-1 (Earth Resistance); IEC61557-5 (Soil Resistivity); JJG 366-2004 (Earth Resistance Meter); JJG 1054-2009 (Clamp-on Earth Resistance Meter).

Mechanical parameters

Dimensions (L×W×H) (mm)	277.2mm×227.5mm×153mm
Size of clamp(L×W×H) (mm)	101mm×27mm×214mm
Standard Test Wire	4 wires: each for red 15m, black 15m, yellow 10m, and green 10m
Simple Test Wire	2 wires: each for yellow 1.5m and green 1.5m
Auxiliary Grounding Rod	4 wires: Φ10mm×200mm Over 5000 times (Short-circuit test, interval time should be at least 30 seconds)
1000A current clamp(Optional)	2pcs :1 blue-banana plug and 1 blue-audio plug. 50mm diameter,1000:1,
Weight (kg)	Total weight: 7.6kg (including package) Tester: 1975g (including battery) Testing wires: 1300g Auxiliary grounding rods: 850g (4pcs) Current clamp: 940g(2 pcs) optional

Environmental conditions

Operating temperature	-10°C to +50°C
Storage temperature	-40°C to 70°C
Relative humidity	≤90%RH